

Verification of mathematical model of solid with defects under dynamic loading

Bayandin Yu V[®], Bilalov D A and Uvarov S V

Institute of Continuous Media Mechanics of the Ural Branch of the Russian Academy of Sciences, Academician Korolev Street 1, Perm 614013, Russia

[®] buv@icmm.ru

The previously developed mathematical model of a solid with mesoscopic defects was validated on the comparison with experimental data from dynamic tests, including the Hopkinson-Kolsky test and shock-wave loading. The proposed constitutive relations (equations of state) allow the description of the deformation behavior of typical elastoviscoplastic materials (metals and alloys) in a wide range of strain rates, temperatures and stresses. Techniques for estimation of identifying parameters of the model have been developed and based on solving a number of independent problems of minimizing the residuals between the calculated and experimental data. During identification procedure, both literature data and author's experiments were used. An experiment was carried out on high-speed collision of a cylindrical sample with a rod (Taylor-Hopkinson test) combined with registration of the temperature field. The comparison was carried out by numerical modeling using the finite element method in both three-dimensional and axisymmetric formulations. The results of numerical calculations are in good agreement with the experiments performed: the shape of the rod after collision and the measured temperature (dissipation of mechanical energy during inelastic deformation) coincide. This testifies to the adequacy of the developed mathematical model and indicates the possibility of its application for solving problems in solid mechanics.

The reported study was funded by Russian Foundation for Basic Research and Perm region, projects No. 19-48-590009 and No. 19-48-590016.