

# Sessile drop and bubble capillary oscillation study

Sergeev I N<sup>1,®</sup>, Akhmatov Z A<sup>1</sup> and Khokonov A Kh<sup>2,1</sup>

<sup>1</sup> Kabardino-Balkarian State University, Chernyshevskogo Street 173, Nalchik 360004, Russia

<sup>2</sup> Institute for Nuclear Research of the Russian Academy of Science, Prospekt 60-letiya Oktyabrya 7a, Moscow 117312, Russia

<sup>3</sup> Kabardino-Balkar Scientific Center of the Russian Academy of Sciences, Inessa Armand 37, Nalchik 360051, Russia

® pirlfix@mail.ru

The dynamical method for measuring interfacial tension liquid metals-solid substrates by means of capillary vibration excitation is implemented. Both droplet-substrate fixed and mobile contact line are investigated. Fixed contact line can be realized for contact angle less than 90 and for small surface vibration amplitudes, otherwise the second case takes place. The capillary frequencies for fixed contact line do not depend on substrate properties while for mobile contact line the frequency depends on not only liquid-gas tension but on liquid-substrate tension too. The resonance frequencies of vibrations of gallium microdroplets and its eutectic alloys on substrates of pyrite, highly oriented graphite, and gallium selenide have been obtained. The interpretation of the experimental results was carried out within the framework of approach with used Green's function in analytical form [1]. For the mobile contact line, the eigenfrequencies were found within numerically approaches that have been developed in the work [2].

## Acknowledgments

This work was supported by grant No. MK-927.2022.1.2 from the President of the Russian Federation.

[1] Strani M and Sabetta F 1984 *J. Fluid Mech.* **141** 233–247

[2] Sakakeeny J and Ling Y 2021 *Phys. Fluids* **33** 062109